

Washer Ultra Dry

WASCOMAT WUD SERIES

Combining world-class reliability with innovative features and programmability, **Wascomat washers are designed to work as a system with Wascomat dryers.** The washer initiates the drying process which means, the higher the G-force, the more water is extracted from the laundry. This speeds up the drying process, saving energy, time, and money.



Wash and dry in less than an hour with Wascomat WUD Washers. You will also save energy and up to 50% on water – automatically.

- Save up to 50% on water with Automatic Savings (AS)
- Compass Pro lets you control important functions such as exact water levels, wash times and number of rinses – with a simple turn of the dial
- Robust door handle – durable in any environment
- Door unlocks immediately at the end of final cycle – no delays
- Unique 4-compartment supply dispenser
- Extended machine life with Super Balance
- Provisions to connect up to 5 liquid supplies
- Smart Dosing technology automatically adjusts the ratio of laundry chemicals to water resulting in lower costs, a superior wash, and longer linen life
- Interchangeable parts from one machine size to another

Features and Benefits

Wascomat Compass Pro provides the ultimate in flexibility:

- Up to 48 cycles, 15 custom
- Customize wash programs to lower costs and increase productivity
- Display wash program information in multiple languages
- Reduce operator error by displaying only the programs you use.
- One control knob for easy program selection
- Built-in diagnostics and detailed statistics
- Smart Start – real-time clock for delayed start

Combine Automatic Savings and Smart Dosing for Best Results and Greater Savings

An estimated 60-70% of washers are underloaded, wasting water, chemicals, and energy. That's why Wascomat developed Automatic Savings (AS), a unique feature that automatically matches water consumption to load size. Combine that with Smart Dosing which adjusts laundry chemicals to water ratio, and you will see immediate savings and superior wash results – every time, automatically.

High Speed Extraction

The perfect balance of speed, performance, and BIC savings. High-speed spin removes more water for faster drying times and better wash performance.

Soft Mount Technology for Easy Installation and Faster Drying

Soft-mount technology allows WUD Series washers to be installed on wood floors, upper floors, and over basements.

**WUD718****WUD730****WUD745****WUD760****WUD780**

DRY WEIGHT CAPACITY (LB/KG)	18 8	30 14	45 20	60 27	80 36
WIDTH (IN/MM)	28 3/8 720	35 13/16 910	38 13/16 970	40 3/8 1020	40 3/8 1020
DEPTH (IN/MM)	28 3/8 720	32 3/8 820	37 3/8 945	39 990	44 1/8 1135
HEIGHT (IN/MM)	44 1/8 1135	52 3/8 1345	56 3/8 1430	57 1/8 1465	57 1/8 1465
HEIGHT TO BOTTOM OF DOOR (IN/MM)	14 3/8 360	17 3/8 440	18 1/2 470	19 1/8 500	19 1/8 500
DOOR OPENING DIAMETER (IN/MM)	12 3/8 310	15 3/8 395	17 3/8 435	17 3/8 435	17 3/8 435
CYLINDER VOLUME (FT³/L)	3.6 75	4.6 130	6.4 180	8.5 240	10.6 300
DRAIN OUTLET DIAMETER (IN/MM)	1 1/8 50 3 75	3 75	3 75	3 75	3 75
HEIGHT TO CENTERLINE OF DRAIN (IN/MM)	3 1/8 100	4 3/8 105	4 3/8 105	4 3/8 105	4 3/8 105
EXTRACTION (G-FORCE)	1098 / 350	980 / 350	930 / 350	890 / 350	820 / 300
DYNAMIC LOAD (LB/KN)	417 +/- 110 1.9 +/- 0.5	703 +/- 114 3.1 +/- 0.5	944 +/- 221 4.2 +/- 1	1158 +/- 221 5.2 +/- 1	1387 +/- 292 6.2 +/- 1.3
DYNAMIC FREQUENCY (HZ)	20.8	18.6	17.6	16.8	15.8
NOISE LEVEL (DBA)	<73	<78	<84	<83	<82
CRATED WIDTH (IN/MM)	29 1/8 760	37 13/16 960	40 3/8 1020	41 3/8 1050	41 3/8 1050
CRATED DEPTH (IN/MM)	32 1/2 825	37 13/16 960	41 3/8 1050	42 1/8 1090	47 3/4 1200
CRATED HEIGHT (IN/MM)	50 1270	58 1/8 1490	61 13/16 1570	63 1600	63 1600
CRATED WEIGHT (LB/KG)	373 170	611 278	816 371	974 443	1274 580

ELECTRICAL REQUIREMENTS (STANDARD)

STANDARD VOLTAGES (V/Hz/Ø)	208 - 240 60 1				
POWER (KW) / CKT BREAKER (A) 240V	0.9 / 15	1.5 / 15	2.5 / 15	2.6 / 15	3.5 / 20
VOLTAGE/FREQUENCY/PHASE	120/60/1	120/60/1	N/A		
POWER (KW) / CKT BREAKER (A) 120V	1 / 15	1.6 / 20	N/A		

WATER INFORMATION

INLET FITTINGS (* = 3 INLETS)	3/4 DN20	3/4 DN20	3/4* DN20*	3/4* DN20*	3/4* DN20*
FLOW (GPM/LPM @ 45 PSI) (EACH INLET)	5 20	5 20	5 20	16 60	16 60
RECOMMENDED WATER PRESSURE (PSI/KPA)	30-90 200-600	30-90 200-600	30-90 200-600	30-90 200-600	30-90 200-600
MODIFIED ENERGY FACTOR	2.3	2.4	2.4	2.4	2.4
WATER FACTOR (GAL PER CYCLE/DRUM VOLUME)	3.8	3.5	3.5	3.9	3.9

Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper floor or above-basement installations. Contact Laundrylux for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.

Laundrylux**800.645.2204 • laundrylux.com**

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0938

Sales & Administration: 516-371-4400 • F 516-371-4204 • sales@laundrylux.com

Parts: 516-371-2000 • F 516-371-4029 • parts@laundrylux.com

Tech Support: 516-371-0700 • F 516-371-4029 • service@laundrylux.com

En Mexico: Llame gratis a este número 001-800-010-1010

**Contact us today to learn more about our new products and technologies.**